

Jacuzzi J-345

Specifications

Seating Capacity.....	6-7 Adults
Dimensions	84" x 84" x 36" (214 cm x 214 cm x 92 cm); For Complete Dimensions, See page 75
Dry Weight.....	777 lbs (352 kg)
Filled Weight (Average Fill).....	3,654 lbs (1,657 kg)
Water Capacity (Average Fill)	345 US gallons (1,306 Liters)
Electronic Controls	Solid state electronic touchscreen controls, programmable temperature, filtration, and heat cycles
Pump 1	North America (60 Hz): 1-Speed, 4.8 HP brake, 2.5 HP continuous, 56 Frame
Export (50 Hz):	1-Speed, 2.0 HP continuous
Pump 2	North America (60 Hz): 1-Speed, 4.8 HP brake, 2.5 HP continuous, 56 Frame
Export (50 Hz):	1-Speed, 2.0 HP continuous
Circulation Pump.....	Yes, 8-hour
Heater	North America (60 Hz): 5.5kW High Flow
Export (50 Hz)	2.7kW High Flow
Total Jacuzzi® PowerPro® Jets	41
Seat A Jets	4 Jacuzzi® PowerPro® FX, 2 Jacuzzi® PowerPro® FX Large Rotational, 2 Jacuzzi® PowerPro® FX Small
Seat B Jets	2 Jacuzzi® PowerPro® FX
Seat C Jets	3 Jacuzzi® PowerPro® MX, 2 Jacuzzi® PowerPro® FX Rotational, 2 Jacuzzi® PowerPro® FX Small
Seat D Jets	1 Jacuzzi® PowerPro® FX Large Rotational
Seat E Jets (Standard model).....	10 Jacuzzi® PowerPro® FX, 2 Jacuzzi® PowerPro® FX Small
Seat E Jets (optional IR Therapy)	8 Jacuzzi® PowerPro® FX, 2 IR Therapy Lights, 2 Jacuzzi® PowerPro® FX Small
Seat E HYDROSOOTHE™ Jets.....	2 Jacuzzi® PowerPro® FX Directional with independent flow rate valve
Seat F Jets.....	2 Jacuzzi® PowerPro® FX Large, 2 Jacuzzi® PowerPro® FX Rotational, 2 Jacuzzi® PowerPro® FX, 2 Jacuzzi® PowerPro® FX Small
Footwell (G).....	8 Jacuzzi® PowerPro® FX Mini, 1 Jacuzzi® PowerPro® FX
Massage Selectors	2
Air Controls.....	4, On/Off rocker style
Water Management System.....	Two 60 ft² filter cartridges; filter 1 on 8-hour circulation pump; filter 2 on jets pump 1; Factory installed ClearRay Active Oxygen® System; Optional True Water® System
Export (50 Hz):	ClearRay Active Oxygen® System
LED Lighting	One underwater light with 4 color modes, one colored waterfall light, cup holders, 2 HYDROSOOTHE pillow lights, and exterior lights
ProFinish™ Cabinet Colors.....	Modern Hardwood, Brushed Gray, and Smoked Ebony
Acrylic Colors	Platinum, Silver Pearl, Morning Mist, Midnight, Canyon, Monaco (while quantities last)
Headrests	4
Waterfall	One independent flow rate (on or off) adjustment; powered by the circulation pump
Heater:	North America (60 Hz): 5.5 kW, High Flow
Export (50 Hz):	High Flow, 2.7 kW
Electrical Requirements:.....	North America (60 Hz): 240 VAC@40A, 50A, or 60A Export (50 Hz): 220-240 VAC@1x32A, 1x20A/1x16A, 3x16A, or suitably rated circuit breaker to comply with local electrical codes. Certain countries may require dual power inputs; two GFCI RCD breakers are required for this configuration.
Warranty*.....	North America (60 Hz): 10 Years Shell, 7 Years Shell Surface, 5 Years for Plumbing Component Leaks, 5 Years Equipment and Controls, 5 Years Cabinet, 2 Years Jets, 2 Years Lights, 1 Year Stereo; Export (50 Hz): 10 Years Shell, 7 Years Shell Surface, 5 Years Plumbing Component Leaks, 5 Years Equipment and Controls, 5 Years Cabinet, 2 Years Jets, 2 Years Lights, 2 Years Stereo
Special Features (Standard)	SmartTub® Module
Export (50 Hz) (Optional):	SmartTub® Module
Special Features (Optional)	2 IR Therapy Lights
Audio System (Optional).....	BLUEWAVE® Spa Stereo System (Bluetooth/Aux compatible) with four speakers and subwoofer




Shown with the optional IR Therapy Lights

Jacuzzi J-345

Operation/Seat Depths

Note: Shown with the optional IR Therapy Lights



Waterfall is always on when the circulation pump is activated, but can be turned off at the waterfall.

41 Total Jets



Spa Operation Subject to Change without Notice

Seat Depths

A = 25.25" (64.1 cm)
B = 25.25" (64.1 cm)
C = 25.13" (63.8 cm)
D = 23.50" (59.7 cm)
E = 28.50" (72.4 cm)

F = 25.13" (63.8 cm)
G = 16.75" (42.5 cm)
H = 33.50" (85.1 cm)


Listed dimensions represent distance from top of acrylic to lowest point in seat.
Tolerance $\pm 0.5"$ (1.27 cm).




Dimensions/Specifications are Subject to Change Without Notice

Jacuzzi J-345

Dimensions



IMPORTANT! Always measure each hot tub for exact dimensions BEFORE designing its foundational support and/or decking.



Dimensions/specifications subject to change without notice. Tolerance $\pm 0.5"$ (1.27 cm)